



Shaft Specifications

WA Range

Pentacross W-6WA



| Flex | Length (inch) | Weight | Tip Diameter | Butt Diameter | Torque |
|------|---------------|--------|--------------|---------------|--------|
| SR | 46 | 66.5 | 0.336 | 0.610 | 4.0 |
| S | 46 | 67.0 | 0.336 | 0.612 | 3.9 |
| X | 46 | 68.5 | 0.336 | 0.616 | 3.8 |

Pentacross W-7WA



| Flex | Length (inch) | Weight | Tip Diameter | Butt Diameter | Torque |
|------|---------------|--------|--------------|---------------|--------|
| S | 46 | 71.0 | 0.336 | 0.614 | 3.9 |
| X | 46 | 74.0 | 0.336 | 0.620 | 3.5 |

Pentacross W-8WA



| Flex | Length (inch) | Weight | Tip Diameter | Butt Diameter | Torque |
|------|---------------|--------|--------------|---------------|--------|
| S | 46 | 81.5 | 0.336 | 0.612 | 3.9 |
| X | 46 | 85.5 | 0.336 | 0.618 | 3.5 |



BA Range

Pentacross W-5BA



| Flex | Length (inch) | Weight | Tip Diameter | Butt Diameter | Torque |
|------|---------------|--------|--------------|---------------|--------|
| R | 46 | 57.0 | 0.336 | 0.608 | 5.5 |
| SR | 46 | 60.0 | 0.336 | 0.610 | 5.4 |
| S | 46 | 64.0 | 0.336 | 0.616 | 4.8 |

Pentacross W-6BA



| Flex | Length (inch) | Weight | Tip Diameter | Butt Diameter | Torque |
|------|---------------|--------|--------------|---------------|--------|
| SR | 46 | 67.0 | 0.336 | 0.616 | 4.0 |
| S | 46 | 69.0 | 0.336 | 0.618 | 3.9 |
| X | 46 | 74.0 | 0.336 | 0.626 | 3.8 |

Pentacross W-7BA



| Flex | Length (inch) | Weight | Tip Diameter | Butt Diameter | Torque |
|------|---------------|--------|--------------|---------------|--------|
| S | 46 | 75.0 | 0.336 | 0.624 | 3.9 |
| X | 46 | 79.5 | 0.336 | 0.628 | 3.5 |

